

P-6035/10 & P-6035/15 Headset

Art. No. 4000014774 & 4000017147



DESCRIPTION:

The P-6035/10 & P-6035/15 are hearing protective headsets for use together with Intercom Systems in noisy environments. The headset is equipped with high attenuating shells with optimized acoustic design and excellent space for the ears, providing the best possible sound quality and comfort. The headset comes with a quick positioning noise cancelling boom microphone. The headset is equipped with an ON/OFF hook switch.

FEATURES:

- Excellent noise-cancelling
- High attenuating ear shells
- 10m or 15m cable
- Hook switch



ELECTRICAL SPECIFICATIONS:

Termination	Flying leads
Microphone	Dynamic, Noise Cancelling (12dB), 230Ω, 4mV, 70-9000Hz
Earphone	50Ω, 81dBA at 0.5V/1kHz
Compass safe distance	>5m

ENVIRONMENTAL SPECIFICATIONS:

Temperature	-15°C to +55°C
Humidity	+93% (at +40°C)
Protection	IP-54 (when in use)
Attenuation rating (HML)	H=33dB / M=32dB / L=24dB
Attenuation rating (SNR)	33 dB

Technical data sheet

P-6035/10 & P-6035/15 Headset

Art. No. 4000014774 & 4000017147

PHONTECH
by ZENITEL GROUP

MECHANICAL SPECIFICATIONS:

Dimension (HxD)	Approximately 200x95 mm
Weight	0.7 kg
Colour	RAL 9006
Cable	14774: 10m flexible durable cable 17147: 15m flexible durable cable
Manufacturer	Zenitel (3M™ Peltor MT7H79A-65)

CERTIFICATES / COMPLIANCES:

Complies to IEC 60945 Marine equipment
The unit has a DNV-GL, ABS, CCS and RMRS type approval
PPE directive 89/686/EEC
Applicable parts of EN352-1:1993

PRODUCT RELATED TO:

ICS 6200	Integrated Communication System
P-6112	Unit without handset, weather protected
P-5111H	Telephone, watertight
P-11220	Bracket for headset

P-6035/10 & P-6035/15 Headset

Art. No. 4000014774 & 4000017147

PHONTECH

by ZENITEL GROUP

DIMENSIONS / LAYOUT

