

2206 LED ATEX Specifications

Unit Information

Model #: 2206 LED ATEX / Item #09050
UPC-IC (12 Digit): 016731090500

Master Pack Dimensions

Weight: 5.8 lbs. (2.6 kg)
Cube: 0.93 ft³ (0.02 m³)
Quantity: 6

Safety Approvals

IECEX Protection Methods
Ex ib IIB T3 Gb
Ex ib IIIB T180°C Db
-5°C ≤ +40°C

ATEX Protection Methods

Ex II 2GD Ex ib IIB T3 Gb Ex ib IIIB T180°C Db -5°C ≤ Ta ≤ +40°C

ZONE 1 BASEEFA

Specifications

Power Source: 4 x 'D' Cell Alkaline
Light Source: LED
Life: 30,000 hrs
Runtime: 95 hrs
Light Output: 90 Lumens

Unit Dimensions

Length: 8.2 in. (20.9 cm)
Width: 4.9 in. (12.4 cm)
Height: 5.6 in. (14.2 cm)

Approved For use with Duracell MN1300 or
Energizer E95 cells only



WorkSafe™ Model # 2206LED ATEX

Product Features

- For use in hazardous atmospheres
- Waterproof, IP 67 rating
- 'D' Cell Alkaline Batteries
- Switch Guard protects switch on impact
- Glove friendly handle

