



[SDS & TDS](#) | 
 [Search Part #](#) | 
 [Home](#) | 
 [Contact Us](#) |

[INDUSTRIES](#) | 
 [PRODUCT LINES](#) | 
 [A-Z INDEX](#) | 
 [REFERENCE](#) | 
 [WHERE TO BUY](#) | 
 [CORPORATE](#)

**LUBE NCS-30 ECF** is a premium quality, nonmetallic compound containing chemically inert fibers and EXTREME SSURE and ANTI-WEAR additives. These are blended into Lube's biodegradable base compound, which gives a wide temperature range, superior adhesion to wet steel surfaces, resistance to water wash off and ability to withstand invert and high pH muds.

- EFITS:**
- Biodegradable, no bioaccumulation potential-free and non-toxic
  - "Yellow" HOCNF in the Norwegian sector of the North Sea
  - "E" classification in the UK
  - Contains no metals
  - Excellent performance on high-chrome or nickel alloys
  - Nonconductive for MWD applications
  - Protection on Wedge Thread
  - Used on premium/proprietary thread
  - Contains no detectable, leachable, volatile organics by EPA

**NCS-30® ECF™**  
 Drill String Compound



**Description**

Ospar Commission-HOCNF (Harmonized Offshore Chemical Notification Format)  
 CLASSIFICATION: "Yellow" rating for Norway  
 CLASSIFICATION: "E" for the United Kingdom & the Netherlands

**Certifications**



Nonmetallic compound containing chemically inert fibers. Extreme pressure and anti-wear additives and withstands invert and high pH muds. Achieves a substitution warning-free HOCNF rating. Excellent protection against seizing and galling with a consistent rig floor make up.

**Applications**

Designed for optimum performance on all Rotary-Shouldered connections such as Tool Joints and Drill Collars. It can also be used on premium/proprietary thread designs such as Double-Shouldered, Wedge Thread™\*, and other types of mechanical seal designs.

Code #	Size	Service Rating	SDS	TDS	Get Assistance
23715	5 gal. pail				
23715L	5 gal lined pail	-10°F to 500°F			
23729	50 gal. drum	-23°C to 260°C			

Also available in an **Arctic** Formulation

Also available as an **Oilfield** Formulation

Free Ph: 1-800-538-5823