

2224LED Specifications

Unit Dimensions

Length: 10.2 in. (25.1 cm) Width: 2.3 in. (5.8 cm) at head

Unit Information

Model #: 2224LED / Item # 15720 UPC-IC (12Digit): 016731157203

Master Pack Dimensions

Weight: 10.8 lbs. (4.9 kg) Cube: $1.43 \text{ ft}^3 (0.04 \text{ m}^3)$

Quantity: 24

Specifications

Power Source: 3 x 'D' Cell Alkaline

Light Source: LED Life: 30,000 hrs Runtime: 250 hrs

Beam Distance: 88 meters Light Output:60 Lumens


Weight (Without batteries): 6.0 oz (.17 kg)

Product Features


- For use in hazardous atmospheres
- 'S' Biner included for quick attachment
- Waterproof, IP 67 rating
- 'Switch Guard' prevents accidental lighting
- · Anti-roll tube
- · Faceted reflector for more light
- Three way switch: On-Momentary-Off

Safety Approvals

UL Protection Methods Intrinsically Safe Divisions 1 & 2 Class I, II, III Div 1 Groups A-G Class I, II, III Div 2 Groups A-G Operating Temp T5



250h






Impact



Beam





WorkSafeTM Model #2224LED

Accessories **Description**

6 1/2" Red Snap In Wand 23853 23860 6 1/2" Yellow Snap In Wand



